BOREHOLE No. BH14

Project: Port Latta Waste Depot
Location: Port Latta
Job No: VT30318

Client: Circular Head Council
Start - Finish Date: 03/2/05 - 03/2/05
Bore dia: 130 mm

Driller: BFP
Rig: Proline Auger Rig
Surface Conditions:

Northings: 5475567.1mN
Eastings: 362361.0mE
RL: 43.0

Logged: DB
Checked:
Oriented: -90

LABORATORY DATA						FIELD DATA			SOIL DESCRIPTION		SOIL CONDITION		COMMENTS
dry density (t/m³)	moisture content (%)	liquid limit (%)	plasticity index (%)	percent fines (%)	design / test data	field & other tests	sample type field tests	ground water depth (m)	graphic log	soil type, unified classification, colour, structure, particle characteristics, minor components	consistency/ density	moisture condition	drilling method, well construction, water and additional observations
										Silty CLAY: medium to high plasticity, orange/brown mottled orange and red, trace of fine grained siltstone gravel.	St to VSt	D	Backfill
								1		Silty CLAY: as above, pale yellow mottled grey and red.	F to VSt	M to D	
								2					
										BH14 terminated at 2.5 metres under to auger refusal on highly weathered siltstone bedrock.			
								3					
								4					
								5					

LABORATORY DATA
- UQN Unconfined Comp. (Natural)
- UQC Unconfined Comp. (Compacted)
- TQN Uncons. Undrained Triax. (Natural)
- TQC Uncons. Undrained Triax. (Compacted)
- TRX Consolidated Undrained Triaxial with pwp measurement
- PSA Particle Size Analysis
- CS 1D oedometer Test
- LPM Laboratory Permeability

FIELD DATA ABBREVIATIONS
- Suv = Uncorrected vane shear (kPa)
- Sup = Pocket penetrometer (kPa)
- N = SPT blows per 300mm
- FPM = Field permeability

GROUNDWATER SYMBOLS
- = Water level (static)
- = Water level (during drilling)
- = Outflow / Inflow

FIELD DATA SYMBOLS
- = Shear vane test
- = Pocket Penetrometer test
- = Standard Penetration Test (SPT top = start of N blowcount)
- = SPT Spoon Sample (Pushed)
- = Undisturbed Tube Sample
- = Disturbed Sample
- = Bulk Sample

DENSITY (N-value)

VL	(very loose)	0 - 4
L	(loose)	4 - 10
MD	(medium dense)	10 - 30
D	(dense)	30 - 50
VD	(very dense)	50 - 100
CO	(compact)	>50/150mm

MOISTURE CONDITION
D = Dry M = Moist W = Wet

CONSISTENCY (Su)

VS	(very soft)	< 12 kPa
S	(soft)	12 - 25
F	(firm)	25 - 50
St	(stiff)	50 - 100
VSt	(very stiff)	100 - 200
H	(hard)	> 200 kPa