

Project: RTA Wharf Upgrade
 Location: Bell Bay
 Job No: PI30328

Client: Rio Tinto Aluminum
 Start - Finish Date: 19/02/09 - 19/02/09
 Bore dia: 150/100mm

Driller: Dave
 Rig: Hydropower Scout
 Surface Conditions: Wharf
 Northings: 5446365.8mN
 Eastings: 489043.7mE
 RL: -11.0
 Logged: MT
 Checked: DRAFT
 Oriented: -90

| LABORATORY DATA | | | | | | FIELD DATA | | | SOIL DESCRIPTION | | SOIL CONDITION | | COMMENTS | |
|---------------------------------|----------------------|------------------|----------------------|-------------------|-------------------------------|---------------------|-------------|-------------|------------------------|-------------|--|----------------------|--------------------|---|
| dry density (t/m ³) | moisture content (%) | liquid limit (%) | plasticity index (%) | percent fines (%) | design / test data | field & other tests | sample type | field tests | ground water depth (m) | graphic log | soil type, unified classification, colour, structure, particle characteristics, minor components | consistency/ density | moisture condition | drilling method, well construction, water and additional observations |
| | | | | | | | | | | | Silty CLAY (CL) dark grey | VSt | | |
| | | | | | | 4/8/10 (N=18) | | | | | basaltic black band (2mm) | | | 45cm sample in SPT |
| | | 57 | 33 | 97 | | | | | | | Silty SAND (SM) dark grey, trace black and brown, fine to coarse grained sand | MD | | 45cm sample in push tube |
| | | | | | Direct Shear c=42 φ=24° | | | | | | Silty CLAY (CH) dark grey, trace of fine sand | VSt | | 45cm sample in SPT |
| | | | | | | 5/12/17 (N=29) | | | | | black-brown, trace fine sand | | | 45cm sample in SPT |
| | | 37.2 | 54 | 26 | | 6/9/12 (N=21) | | | | | SAND (SP) dark grey, fine to coarse grained sand, trace non plastic fines | D | | |



SKM 001 SOIL RTA_GEOTECH_2008 REV_04 300409.GPJ SKM_001_2008 05.07_DS.GDT 5/5/09

| LABORATORY DATA | FIELD DATA ABBREVIATIONS | FIELD DATA SYMBOLS | DENSITY (N-value) | CONSISTENCY (Su) |
|--|--|--|---------------------------|----------------------------|
| UQN Unconfined Comp. (Natural) | S _{uv} = Uncorrected vane shear (kPa) | ✕ = Shear vane test | VL (very loose) 0 - 4 | VS (very soft) < 12 kPa |
| UQC Unconfined Comp. (Compacted) | Sup = Pocket penetrometer (kPa) | ⊥ = Pocket Penetrometer test | L (loose) 4 - 10 | S (soft) 12 - 25 |
| TQN Uncons. Undrained Triax. (Natural) | N = SPT blows per 300mm | ▽ = Standard Penetration Test (SPT top = start of N blowcount) | MD (medium dense) 10 - 30 | F (firm) 25 - 50 |
| TQC Uncons. Undrained Triax. (Compacted) | FPM = Field permeability | ▼ = SPT Spoon Sample (Pushed) | D (dense) 30 - 50 | St (stiff) 50 - 100 |
| TRX Consolidated Undrained Triaxial with pwp measurement | | ■ = Undisturbed Tube Sample | VD (very dense) 50 - 100 | VSt (very stiff) 100 - 200 |
| PSA Particle Size Analysis | | ● = Disturbed Sample | CO (compact) >50/150mm | H (hard) > 200 kPa |
| CS 1D oedometer Test | | □ = Bulk Sample | | |
| LPM Laboratory Permeability | | | | |
| | GROUNDWATER SYMBOLS | | | |
| | ▼ = Water level (static) | | | |
| | ▽ = Water level (during drilling) | | | |
| | → = Outflow / Inflow | | | |
| | | | MOISTURE CONDITION | |
| | | | D = Dry M = Moist W = Wet | |

Project: RTA Wharf Upgrade
 Location: Bell Bay
 Job No: PI30328

Client: Rio Tinto Aluminum
 Start - Finish Date: 19/02/09 - 19/02/09
 Bore dia: 150/100mm

Driller: Dave
 Rig: Hydropower Scout
 Surface Conditions: Wharf
 Northings: 5446365.8mN
 Eastings: 489043.7mE
 RL: -11.0
 Logged: MT
 Checked: DRAFT
 Oriented: -90

| LABORATORY DATA | | | | | | FIELD DATA | | | SOIL DESCRIPTION | | SOIL CONDITION | | COMMENTS | |
|---------------------------------|----------------------|------------------|----------------------|-------------------|--------------------|---------------------|-------------|-------------|------------------------|-------------|--|----------------------|--------------------|---|
| dry density (t/m ³) | moisture content (%) | liquid limit (%) | plasticity index (%) | percent fines (%) | design / test data | field & other tests | sample type | field tests | ground water depth (m) | graphic log | soil type, unified classification, colour, structure, particle characteristics, minor components | consistency/ density | moisture condition | drilling method, well construction, water and additional observations |
| | | | | 10 | | 4/14/26 (N=40) | ● | ▽ | 21 | | SAND (SP) dark grey, fine to coarse grained sand, trace non plastic fines (continued) | | | change in drilling rate 45cm sample in SPT |
| | | | | | | | | | 22 | | Borehole terminated in SAND at 21.75m | | | |
| | | | | | | | | | 23 | | | | | |
| | | | | | | | | | 24 | | | | | |
| | | | | | | | | | 25 | | | | | |
| | | | | | | | | | 26 | | | | | |
| | | | | | | | | | 27 | | | | | |
| | | | | | | | | | 28 | | | | | |
| | | | | | | | | | 29 | | | | | |
| | | | | | | | | | 30 | | | | | |

| | | | | |
|---|--|---|---|---|
| LABORATORY DATA UQN Unconfined Comp. (Natural) UQC Unconfined Comp. (Compacted) TQN Uncons. Undrained Triax. (Natural) TQC Uncons. Undrained Triax. (Compacted) TRX Consolidated Undrained Triaxial with pwp measurement PSA Particle Size Analysis CS 1D oedometer Test LPM Laboratory Permeability | FIELD DATA ABBREVIATIONS Suv = Uncorrected vane shear (kPa) Sup = Pocket penetrometer (kPa) N = SPT blows per 300mm FPM = Field permeability GROUNDWATER SYMBOLS ▼ = Water level (static) ▽ = Water level (during drilling) ↗ ↘ = Outflow / Inflow | FIELD DATA SYMBOLS X = Shear vane test ⊥ = Pocket Penetrometer test ▽ = Standard Penetration Test (SPT top = start of N blowcount) ▼ = SPT Spoon Sample (Pushed) ■ = Undisturbed Tube Sample ● = Disturbed Sample □ = Bulk Sample | DENSITY (N-value) VL (very loose) 0 - 4 L (loose) 4 - 10 MD (medium dense) 10 - 30 D (dense) 30 - 50 VD (very dense) 50 - 100 CO (compact) >50/150mm | CONSISTENCY (Su) VS (very soft) < 12 kPa S (soft) 12 - 25 F (firm) 25 - 50 St (stiff) 50 - 100 VSt (very stiff) 100 - 200 H (hard) > 200 kPa MOISTURE CONDITION D = Dry M = Moist W = Wet |
|---|--|---|---|---|