Ref No 7640

2 0072

No 3 Line of Bores — Section 1351

ALLUVIAL BORING, MT. CAMERON.

35.

North of Watt

Boring commenced 30th Octr. 1901 — No. of Bore 17 {543 chns from No 1 Bore} — Locality Central Stuarts Creek

AMG 589600E 5464300N — No Core held.

Nature of Strata.	Size of Bore.	Depth bored. Since last Report.	Depth bored. Total Depth.	Below Datum.	Running Time.	Prospects obtained.	Description of Strata and Remarks.
		feet. in.	feet. in.	feet. in.		lbs. c. yd.	
Fixed Datum 500 feet. Previously reported			Collar of Bore at Surface	30-84			
	4¼"	1-0	1-0	31-84			Turf
	8	24-3	25-3	56-09			Fine drift with 18" grey cement
	3⅜"	2-3	27-6	58-34			Grey pug
		6-0	33-6	64-34			Dark drift
		5-0	38-6	69-34			Carb siet & lignite
		8-0	46-6	77-34			Grey pug & drift
		2-9	49-3	80-09			Carb siet & lignite
		33-9	83-0	113-84	50 hours		Fine drift with 4'5" pug
		18-6	101-6	132-34			Carb siet & lignite with 9" pyrite
		1-0	102-6	133-34			Soft granite bored into 1 foot
							Total depth of bore to bed rock 101' 6"

Boring rather difficult, bed rock 9 feet lower than at No 16 bore the outcropping Slate Country is not far to the N.W. there is but little chance of getting the gutter trending in that direction now: we will however go on to the 62 chain peg as surface of ground is falling, before turning back to Muscleboro

W. J. Griffin
Inspected by Mines
6 Nov. 1901

GOVERNMENT GEOLOGIST 1007 1 NOV 1901 LAUNCESTON.

MINES DEPT. S.M.D. 01 TASMANIA