






2600
2700
2800
FIRST READING


5cm


2800
CALIBRATION BEFORE SURVEY


04-357














DUAL LATEROLOG
Schlumberger
SPONTANEOUS POTENTIAL
RESISTIVITY
LATEROLOG DEEP Rxo
LATEROLOG SHALLOW Rxo
REPEAT SECTION
MAIN PASS
CALIBRATION DATA
REPEAT DATA
DUAL LATEROLOG





INDUCTION
CORRELATION CURVES
Customer: Anadarko - El Paso
Well: Crown A-5
Field: Crown Pinnacle - Delhi
Date: 4/1/
Depth Control Log Type:
Type Log
Run No.
Date Logged
Recorded By
Witnessed By
Bit Size
Type Fluid in Hole
Max. Rec. Temp.
Equip. Location
Recorded By
Witnessed By
Run No.
Date
Depth-Driller
Depth-Logger
Bottom Logged Interval
Top Logged Interval
Type Fluid in Hole
Salinity
Density
Level


CORRELATION CURVE
DIP ANGLE AND DIRECTION
CLUSTER PEBBLES WITH HIGHER PERMEABILITY
AND DIPPING AT 180°/90±5.8 DE (102 FT/80)102 FT DIPP
CLUSTER PEBBLES ABOVE PLOT 1.2 (240)3 PEBBLES
RESULTS PEBBLES ABOVE 4°DOWN 5.5 DEGREES S5.5E ANGLE
BLACK ARROWS ARE 'PEBBLES' 2 (240)5 ARE ABOVE
PEBBLES ANGLE (ALL)ALL RESULTS
10 FT. A N FT. - 30 DEVN A 1
REFERENCE (0A250)-00
1996 FEBR. 0207 TO 0674
DEVIATION ORIENT
9100
9150
9200
9250
9300
9350
9400
9450
9500
9550
9600
9650
9700
9750
9800
9850
9900
9950
10000

9700
9800
9900
10000
10100
10200
10300
10400
10500
10600
10700
10800
10900
11000
11100
11200
11300
11400
11500
11600
11700
11800
11900
12000
12100
12200
12300
12400
12500
12600
12700
12800
12900
13000
13100
13200
13300
13400
13500
13600
13700
13800
13900


8700
8800
8900
9000
9100
9200
9300
9400
9500
9600
9700
9800
9900
10000
5 cm




REFERENCE 104250.01

POLAR FREQUENCY PLOT

12 FT X 3 FT - 35/DEGR X 1

CLUSTER POOLED RESULTS - 2 LEVELS POOLED


BLACK RESULTS ARE POOLED 2 LEVELS

ALL RESULTS ARE PLOTTED








ZONE FROM 8150 TO 8213
FREQUENCY SCALE - FROM CENTER TO EDGE 3 RESULTS
POLAR SCALE - FROM EDGE TO CENTER 60 DEGREES




ZONE FROM 8217 TO 8274
FREQUENCY SCALE - FROM CENTER TO EDGE 3 RESULTS
POLAR SCALE - FROM EDGE TO CENTER 60 DEGREES




ZONE FROM 8280 TO 8475
FREQUENCY SCALE - FROM CENTER TO EDGE 12 RESULTS
POLAR SCALE - FROM EDGE TO CENTER 60 DEGREES




ZONE FROM 8811 TO 8895
FREQUENCY SCALE - FROM CENTER TO EDGE 3 RESULTS
POLAR SCALE - FROM EDGE TO CENTER 60 DEGREES




ZONE FROM 8901 TO 9059
FREQUENCY SCALE - FROM CENTER TO EDGE 6 RESULTS
POLAR SCALE - FROM EDGE TO CENTER 60 DEGREES




ZONE FROM 9153 TO 9228
FREQUENCY SCALE - FROM CENTER TO EDGE 3 RESULTS
POLAR SCALE - FROM EDGE TO CENTER 60 DEGREES



ZONE FROM 9234 TO 9360
FREQUENCY SCALE - FROM CENTER TO EDGE 6 RESULTS
POLAR SCALE - FROM EDGE TO CENTER 60 DEGREES



ZONE FROM 9441 TO 9519
FREQUENCY SCALE - FROM CENTER TO EDGE 6 RESULTS
POLAR SCALE - FROM EDGE TO CENTER 60 DEGREES


Schlumberger
CONTINUOUS DIPMETER
HIGH RESOLUTION
COUNTRY AUSTRALIA
FIELD or LOCATION WILDCAT
WELL PELICAN 4
COMPANY HEMATITE PETROLEUM
COMPANY HEMATITE PETROLEUM CO.
WELL PELICAN 4
FIELD WILDCAT
COUNTRY AUSTRALIA STATE
REFERENCE 104 250.11
12 FT CLUSTER
35 DEGR X 1
TYPE OF PLOT
TADPOLE
Run No. ONE
Date 8 FEB 79
Depth - Driller 11,477
Depth - Logger 11,477
Btm. log interval 11,477
Top log interval 9000
Casing - Logger 9000
Bit Size 8 1/2"
Type fluid in hole SEAWATER/GEL
Dens. Visc. 9.2 39
pH Fluid loss 10.5 7.2
Source of Sample CIRCULATION
Rm @ Meas. Temp. 2.52 @ 70°F
Rmf @ Meas. Temp. 2.08 @ 70°F
Rmc @ Meas. Temp. 3.03 @ 70°F
Source: Rmf Rmc CALCULATED
Rm @ BHT 1.71 @ 170°F
Time Since Circ. 12 HRS
Max. Rec. Temp. 170°F
Equip. No. Location 1464 PERTH
Recorded By P. L. HANNAN
Witnessed By P. J. TIERNEY
Permanent Datum Ground Level
Elevation 68
Log Measured from KB
Above Perm. Datum 82
Drilling Measured from KB
Elev.: K.B. 150
D.F. 149
G.L. 68
Run No. ONE
Depth - Driller 11,477
Depth - Logger 11,477
Btm. log interval 11,477
Top log interval 9000
Casing - Logger 9000
Bit Size 8 1/2"
Type fluid in hole SEAWATER/GEL
Dens. Visc. 9.2 39
pH Fluid loss 10.5 7.2
Source of Sample CIRCULATION
Rm @ Meas. Temp. 2.52 @ 70°F
Rmf @ Meas. Temp. 2.08 @ 70°F
Rmc @ Meas. Temp. 3.03 @ 70°F
Source: Rmf Rmc CALCULATED
Rm @ BHT 1.71 @ 170°F
Time Since Circ. 12 HRS
Max. Rec. Temp. 170°F
Equip. No. Location 1464 PERTH
Recorded By P. L. HANNAN
Witnessed By P. J. TIERNEY
Run No. TWO
Depth - Driller 12,017
Depth - Logger 12,017
Btm. log interval 12,017
Top log interval 11,470
Casing - Logger 9000
Bit Size 8 1/2"
Type fluid in hole SEAWATER/GEL
Dens. Visc. 9.2 39
pH Fluid loss 10.5 7.2
Source of Sample CIRCULATION
Rm @ Meas. Temp. 2.52 @ 70°F
Rmf @ Meas. Temp. 2.08 @ 70°F
Rmc @ Meas. Temp. 3.03 @ 70°F
Source: Rmf Rmc CALCULATED
Rm @ BHT 1.71 @ 170°F
Time Since Circ. 12 HRS
Max. Rec. Temp. 170°F
Equip. No. Location 1464 PERTH
Recorded By P. L. HANNAN
Witnessed By P. J. TIERNEY
Run No. THREE
Depth - Driller 12,017
Depth - Logger 12,017
Btm. log interval 12,017
Top log interval 11,470
Casing - Logger 9000
Bit Size 8 1/2"
Type fluid in hole SEAWATER/GEL
Dens. Visc. 9.2 39
pH Fluid loss 10.5 7.2
Source of Sample CIRCULATION
Rm @ Meas. Temp. 2.52 @ 70°F
Rmf @ Meas. Temp. 2.08 @ 70°F
Rmc @ Meas. Temp. 3.03 @ 70°F
Source: Rmf Rmc CALCULATED
Rm @ BHT 1.71 @ 170°F
Time Since Circ. 12 HRS
Max. Rec. Temp. 170°F
Equip. No. Location 1464 PERTH
Recorded By P. L. HANNAN
Witnessed By P. J. TIERNEY
Run No. Run No.
Depth - Driller Depth - Driller
Depth - Logger Depth - Logger
Btm. log interval Btm. log interval
Top log interval Top log interval
Casing - Logger Casing - Logger
Bit Size Bit Size
Type fluid in hole Type fluid in hole
Dens. Visc. Dens. Visc.
pH Fluid loss pH Fluid loss
Source of Sample Source of Sample
Rm @ Meas. Temp. Rm @ Meas. Temp.
Rmf @ Meas. Temp. Rmf @ Meas. Temp.
Rmc @ Meas. Temp. Rmc @ Meas. Temp.
Source: Rmf Rmc Source: Rmf Rmc
Rm @ BHT Rm @ BHT
Time Since Circ. Time Since Circ.
Max. Rec. Temp. Max. Rec. Temp.
Equip. No. Location Equip. No. Location
Recorded By Recorded By
Witnessed By Witnessed By
Permanent Datum
Elevation
Log Measured from
Above Perm. Datum
Drilling Measured from
Elev.: K.B.
D.F.
G.L.
Run No.
Depth - Driller
Depth - Logger
Btm. log interval
Top log interval
Casing - Logger
Bit Size
Type fluid in hole
Dens. Visc.
pH Fluid loss
Source of Sample
Rm @ Meas. Temp.
Rmf @ Meas. Temp.
Rmc @ Meas. Temp.
Source: Rmf Rmc
Rm @ BHT
Time Since Circ.
Max. Rec. Temp.
Equip. No. Location
Recorded By
Witnessed By

COUNTRY
FIELD or
LOCATION
WELL
COMPANY

Other Services

Permanent datum: Elevation: Elev.: K.B. D.F. G.L.
Log measured from: above Permanent datum
Drilling measured from:

Date
Run No.
Depth-Driller
Depth-Logger
Bottom logged interval
Top logged interval
Type fluid in hole
Salinity, PPM Cl
Density
Level
Max. rec. temp. deg. F
Equipment No.
Location
Recorded by
Witnessed by

RUN NO. BIT NO. FROM TO CASING SIZE WEIGHT TYPE FLUID DENSITY VISCOSITY PH FLUID LOSS SOURCE OF SAMPLE RM @ MEAS. TEMP. RMF @ MEAS. TEMP. RMC @ MEAS. TEMP. SOURCE RMF RMC RM @ BHT TIME SINCE CIRC. MAX. REC. TEMP. DEG. F EQUIP. NO. LOCATION RECORDED BY WITNESSED BY

TOOL NUMBER AND TYPE OF COMBINATION USED

DENSITY DATA

| Run No. | Tool Position | Density Source | Density Matrix | Density Hole Corr. | Density Rmf | Density Rmc | Density Rm | Density Rm @ Temp. | Density Max. Rec. Temp. | Density Equip. No. | Density Location | Density Recorded By | Density Witnessed By |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | |

NEUTRON DATA

| Run No. | Tool Position | Neutron Source | Neutron Matrix | Neutron Hole Corr. | Neutron Rmf | Neutron Rmc | Neutron Rm | Neutron Rm @ Temp. | Neutron Max. Rec. Temp. | Neutron Equip. No. | Neutron Location | Neutron Recorded By | Neutron Witnessed By |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | |

LOGGING DATA

| Run No. | Tool Position | Neutron Source | Neutron Matrix | Neutron Hole Corr. | Neutron Rmf | Neutron Rmc | Neutron Rm | Neutron Rm @ Temp. | Neutron Max. Rec. Temp. | Neutron Equip. No. | Neutron Location | Neutron Recorded By | Neutron Witnessed By |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | |

Density Source | Density Matrix | Density Hole Corr. | Density Rmf | Density Rmc | Density Rm | Density Rm @ Temp. | Density Max. Rec. Temp. | Density Equip. No. | Density Location | Density Recorded By | Density Witnessed By

CALIBRATION DATA

| Run No. | Tool Position | Neutron Source | Neutron Matrix | Neutron Hole Corr. | Neutron Rmf | Neutron Rmc | Neutron Rm | Neutron Rm @ Temp. | Neutron Max. Rec. Temp. | Neutron Equip. No. | Neutron Location | Neutron Recorded By | Neutron Witnessed By |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | |

Density Source | Density Matrix | Density Hole Corr. | Density Rmf | Density Rmc | Density Rm | Density Rm @ Temp. | Density Max. Rec. Temp. | Density Equip. No. | Density Location | Density Recorded By | Density Witnessed By

REMARKS

CALIPER
hole diameter in inches

NEUTRON POROSITY %
—.15 matrix

GAMMA RAY
api units

BULK DENSITY
g / cm³

REPEAT SECTION

CALIBRATION DATA

COMPENSATED NEUTRON CALIBRATION CODING

1. MECHANICAL ZERO
2. NEUTRON SENSITIVITY (1000) MEASURED IN UNITS
   PANEL TEST
   NOTE: DO POROSITY 2.65 DO POROSITY 2.65
3. 1 2.4 4.1
   2 2.6 4.3
   3 2.8 4.5
   4 3.0 4.7
4. DENSITY NORMALIZED WITH ONE .4 IN PLATE
5. T.A. TOOL IN SET TO
6. T.A. CALIBRATION WITH .4 IN PLATE
7. T.A. TOOL IN SET TO
   10 .20
   11 .3
   12 .4
   NOTE: POSITIONING 1.27 = METER DIP

FORMATION DENSITY COMPENSATED CALIBRATION CODING


1. MECHANICAL ZERO
2. DENSITY CALIBRATION
   PANEL TEST (DO) LOGGED


| NOTE | DO | LOG |
|---|---|---|
| 1 | 2.55 | 2.55 |
| 2 | 2.65 | 2.65 |
| 3 | 2.75 | 2.68 |
| 4 | 2.95 | 2.68 |
| 5 | 3.05 | 2.68 |


3. MECHANICAL ZERO CHANGE
   SET TOOL
4. SET TOOL
5. TOOL CALIBRATE @ 2.65 = 2.68
6. TOOL CALIBRATE @ 2.65 (1) = 2.68
7. USE POSITION 1.27 (1) = 2.68 (1) = 2.68

GAMMA RAY CALIBRATION CODING

1. MECHANICAL ZERO
2. TEST 1 ELECTRICAL ZERO
3. TEST 2 ELECTRICAL ZERO
4. TOOL CAL. TEST AT API
5. T.A. UNITS =


ALASKA NATIONAL
INTERSTATE
CALIPER
GAMMA RAY
API UNITS
NEUTRON POROSITY %
LIMESTONE
BULK DENSITY
G/CC


GAMMA RAY
API UNITS
CALIPER
hole diameter in inches
BULK DENSITY
grams / cc
NEUTRON POROSITY %
limestone
APPROX. NEUTRON
ON
CALIBRATION DATA
Schlumberger
COMPENSATED NEUTRON
FORMATION DENSITY


COMPENSATED NEUTRON FORMATION DENSITY
CALIPER
hole diameter in inches
NEUTRON POROSITY %
GAMMA RAY
API units
RHOB DENSITY
g/cm³
REPEAT SECTION
CALIBRATION DATA
Schlumberger

= 2·306

7A
7A
7A
6
5
4
3
2
1

GCB-C
13
13
12
11
2
1
GCB-A
13
13
12
11
2
1
7
6
5
4
3
2
1

FDC MASTER
CALIBRATION

PGP-EJ 1065
PGC-EB 923
PDH-DB 902
GSR-B 2973
GCB-C 739


$P_2$ = 724·0

$P_1$ = 402·8

$P_2$ = 773·2

$P_1$ = 437·6

5 cm


COMPENSATED NEUTRON FORMATION DENSITY
CALIPER
hole diameter in inches
GAMMA RAY
api units
NEUTRON POROSITY %
limestone matrix
BULK DENSITY
grams / cc
CORRECTION
REPEAT SECTION
CALIBRATION DATA
COMPENSATED NEUTRON CALIBRATION CODING
MICROMHOS/M
MICROMHOS/M
NEUTRON POROSITY %
FORMATION DENSITY COMPENSATED CALIBRATION CODING
MICROMHOS/M
MICROMHOS/M
GAMMA RAY CALIBRATION CODING
MICROMHOS/M
MICROMHOS/M
CALIBRATION AFTER SURVEY
BEFORE SURVEY
COMPENSATED NEUTRON
FORMATION DENSITY
Schlumberger