

Vessel: M/V Pacific Titan  
 Client: TAP  
 Project #: 6374  
 Area: Bass Strait, Australia T47P

Preplotted LineName: **VVMOL08-011**  
 Contractors Line Name: **VMOL08-011-001**

Direction: **318**  
 Date Shot: **Wednesday, March 1**

Party Chief: Sigurd Østerud Chief Obs: Allan Beattie Observers: Jun Lumabas, Dennis Maranon, Dervin Victorio

FS Time (UTC)	SOLTape#	First File	First Shot	First Shot File	FCSP	FCSP File	FCSP Time (UTC)
5:35	1	979	1740	981	1720	1001	5:38

**Swell Noise Levels**  
 <2% above 25µb

EOL Time (UTC)	EOLTape#	Last File	EOL SP	EOL File	LCSP	LCSP / LFFSP File	LCSP Time (UTC)
7:55	1	1841	881	1840	1001	1720	7:36

<2% above 25µb

	Wind Speed	Swell	Streamer Feather	Filtered Noise	Bottom Speed	Water Speed	Water Depth	Streamer Depth	Source Volume Stbd. Port
<b>SOL</b>	12 kts E	1.5 m E	-5.0 °Port	5 µB	4.8 kts.	5.2 kts.	72 m	8 m	N/A / 3040 cu. in
<b>EOL</b>	12 kts E	1.5 m E	-1.0 ° Port	5.4 µB	5.0 kts.	5.2 kts.	71 m	8 m	N/A / 3040 cu. in

### Recording Parameters

Recording System	Sercel Seal 408XL
Record Length	6000 ms
Sample Rate	2 ms
Start Of Data	50 ms before FTB
Low Cut Filter	4.7 Hz / 12dB Combined
Hi Cut Filter	200 Hz @ 370 dB / Octave
Tape Format	Demux. SEGD rev 1, 8058
Tape Brand	Imation BlackWatch 3590 10Gb
Polarity	First Break is Negative
Shot Point Interval	25m

### Source Parameters

Array Volume	3040 cubic inches
Operating Pressure	2000 psi +/- 10%
Array Configuration	3 Strings
Array Numbering	Stbd to Port / 1 to 3
Array Separation	10m
Source Depth	6 m +/- 1m
Center Source to Nav Mast	180m
Comment	

### Auxiliary Channels

Aux1 System St	Aux4: WB S1	Aux7:
Aux2 FTB	Aux5:	Aux8:
Aux3 450 ms de	Aux6:	Aux9:

### Auxiliary Hydrophone Channels

Array 1	Array 2	Array 3
Aux13: Position 1	Aux19: Position 1	Aux25: Position 1
Aux14: Position 2	Aux20: Position 2	Aux26: Position 2
Aux15: Position 3	Aux21: Position 3	Aux27: Position 3
Aux16: Position 4	Aux22: Position 4	Aux28: Position 4
Aux17: Position 5	Aux23: Position 5	Aux29: Position 5
Aux18: Position 6	Aux24: Position 6	Aux30: Position 6

### Streamer Parameters

Number of Streamers	1
Streamer Length	6000m
Number Channels	480
Group Interval	12.5 m
Operating Depth	8 m +/- 1m
Crossline offset	NA
Offset CSCNG (inline)	145m (Centre of source to centre of near group)

**Line Status: Complete**

### Line Comments

String 1 NFH position 6 (Aux. 18) dead.  
 String 2 NFH position 2 (Aux. 20) dead.  
 String 2 NFH position 3 (Aux. 21) dead.

### Bad Channels

Ch. 91 & 337 failed capacitance.  
 Ch. 242 failed leakage.  
 Ch. 59 reversed polarity.

### Sequence breakdown

Start	End	Status	Comment
1720	881	Prime	VVMOL08-011

### Channels as recorded

AuxChannels: A1-A30  
 Streamer1: 1-480 Streamer4:  
 Streamer2: Streamer5:  
 Streamer3: Streamer6:

GMT	Tape	Drive	File	SP	Event	Remarks
04:57					SoftStart	
	1	1/2	979-980		BOT	Noise files
05:35			981-1000	1740	FSP	Nav run in SPs
05:38			1001	1720	SOL	FCSP
			1328	1393	GUN-BadShot	Autofire detected, header missing
07:36			1720	1001	LCSP	LFFSP
			1799	922	GUN-BadShot	Autofire detected, header missing
07:55			1840	881	EOL	LGSP
	1	1/2	1841		EOT	Noise file

Abbreviations Used

SOL = Start of Line	BOT = Beginning of Tape	FGSP = First Good Shotpoint	FFFSP = First Full Fold Shotpoint	NDR = No Data Recorded
EOL = End of Line	EOT = End of Tape	LGSP = Last Good Shotpoint	LFFSP = Last Full Fold Shotpoint	FCSP = First Chargeable Shotpoint
FA = Feather Angle	SI = Seismic Interference	FOLSP = First Overlap SP	LOLSP = Last Overlap Shotpoint	LCSP = Last Chargeable
NTBP = Not To Be Processed	ITB = Internal Time Break	FTB = Field Time Break		