

Vessel: M/V Pacific Titan
 Client: TAP
 Project #: 6374
 Area: Bass Strait, Australia T47P

Preplotted LineName: **VVMOL08-034**
 Contractors Line Name: **VMOL08-034-004**

Direction: **236**
 Date Shot: **Wednesday, March 1**

Party Chief: Sigurd Østerud Chief Obs: Allan Beattie Observers: Jun Lumabas, Dennis Maranon, Dervin Victorio

FS Time (UTC)	SOLTape#	First File	First Shot	First Shot File	FCSP	FCSP File	FCSP Time (UTC)
18:42	4	979	1582	981	1562	1001	18:45

Swell Noise Levels
 <1% above 25µb

EOL Time (UTC)	EOLTape#	Last File	EOL SP	EOL File	LCSP	LCSP / LFFSP File	LCSP Time (UTC)
20:18	4	1610	970	1593	1001	1562	20:13

<1% above 25µb

	Wind Speed	Swell	Streamer Feather	Filtered Noise	Bottom Speed	Water Speed	Water Depth	Streamer Depth	Source Volume Stbd. Port
SOL	7 kts E	0.5 m Var	4.8 °Starboard	5.1 µB	5.1 kts.	5.2 kts.	72.6 m	8 m	N/A / 3040 cu. in
EOL	8 kts E	0.5 m Var	3.1 ° Starboard	NA µB	5.1 kts.	5.2 kts.	69.5 m	8 m	N/A / 3040 cu. in

Recording Parameters

Recording System	Sercel Seal 408XL
Record Length	6000 ms
Sample Rate	2 ms
Start Of Data	50 ms before FTB
Low Cut Filter	4.7 Hz / 12dB Combined
Hi Cut Filter	200 Hz @ 370 dB / Octave
Tape Format	Demux. SEG D rev 1, 8058
Tape Brand	Imation BlackWatch 3590 10Gb
Polarity	First Break is Negative
Shot Point Interval	25m

Source Parameters

Array Volume	3040 cubic inches
Operating Pressure	2000 psi +/- 10%
Array Configuration	3 Strings
Array Numbering	Stbd to Port / 1 to 3
Array Separation	10m
Source Depth	6 m +/- 1m
Center Source to Nav Mast	180m
Comment	

Auxiliary Channels

Aux1 System St	Aux4: WB S1	Aux7:
Aux2 FTB	Aux5:	Aux8:
Aux3 450 ms de	Aux6:	Aux9:

Auxiliary Hydrophone Channels

Array 1	Array 2	Array 3
Aux13: Position 1	Aux19: Position 1	Aux25: Position 1
Aux14: Position 2	Aux20: Position 2	Aux26: Position 2
Aux15: Position 3	Aux21: Position 3	Aux27: Position 3
Aux16: Position 4	Aux22: Position 4	Aux28: Position 4
Aux17: Position 5	Aux23: Position 5	Aux29: Position 5
Aux18: Position 6	Aux24: Position 6	Aux30: Position 6

Streamer Parameters

Number of Streamers	1
Streamer Length	6000m
Number Channels	480
Group Interval	12.5 m
Operating Depth	8 m +/- 1m
Crossline offset	NA
Offset CSCNG (inline)	145m (Centre of source to centre of near group)

Line Status: Complete

Line Comments

String 1 NFH position 6 (Aux. 18) dead.
 String 2 NFH position 2 (Aux. 20) dead.
 String 2 NFH position 3 (Aux. 21) dead.
 SP 970 - Last Good SP d/t air hose line to reel blown on string 1.
 EOL noise file NA because guns were firing even after guns were switch off.
 File numbers 1594-1610 dummy SPs

Bad Channels

Ch. 91 & 337 failed capacitance.
 Ch. 242 failed leakage.
 Ch. 59 reversed polarity.

Sequence breakdown

Start	End	Status	Comment
1562	970	Prime	VVMOL08-034

Channels as recorded

AuxChannels: A1-A30	
Streamer1: 1-480	Streamer4:
Streamer2:	Streamer5:
Streamer3:	Streamer6:

<i>GMT</i>	<i>Tape</i>	<i>Drive</i>	<i>File</i>	<i>SP</i>	<i>Event</i>	<i>Remarks</i>
18:06					SoftStart	
	4	1/2	979-980		BOT	Noise files
18:42			981-1000	1582-1563	FSP	Nav run in SPs
18:45			1001	1562	SOL	FCSP
20:13			1562	1001	LCSP	LFFSP
20:18			1593	970	EOL	LGSP
	4	1/2	1610		EOT	Noise file

Abbreviations Used

SOL = Start of Line	BOT = Beginning of Tape	FGSP = First Good Shotpoint	FFFSP = First Full Fold Shotpoint	NDR = No Data Recorded
EOL = End of Line	EOT = End of Tape	LGSP = Last Good Shotpoint	LFFSP = Last Full Fold Shotpoint	FCSP = First Chargeable Shotpoint
FA = Feather Angle	SI = Seismic Interference	FOLSP = First Overlap SP	LOLSP = Last Overlap Shotpoint	LCSP = Last Chargeable
NTBP = Not To Be Processed	ITB = Internal Time Break	FTB = Field Time Break		