

Vessel: M/V Pacific Titan  
 Client: 3D Oil  
 Project #: 6374  
 Area: T41P

Preplotted LineName: **TDOB08-007**  
 Contractors Line Name: **TDOB08-007-014**

Direction: **331°**  
 Date Shot: **21 April 2008**

Party Chief: Haydn Brook Chief Obs: Tyrone Hackett Observers: Slawomir Korybalski, John Gracey, Ingvild Bostad

FS Time (UTC)	SOLTape#	First File	First Shot	First Shot File	FGSP	FGSP File	FGSP Time (UTC)	Swell Noise Levels
01:39	18	979	981	981	1001	1001	01:42	<0.8% above 25µb
EOL Time (UTC)	EOLTape#	Last File	EOL SP	EOL File	LFFSP	LFFSP File	LFFSP Time (UTC)	
03:11	18	1554	1553	1553	1433	1433	02:52	<0.8% above 25µb
Wind Speed	Swell	Streamer Feather	Filtered Noise	Bottom Speed	Water Speed	Water Depth	Streamer Depth	Source Volume Stbd. Port
<b>SOL</b> 3 kts. NE	.5m NE	7.5 °Port	4.8 µB	5.1 kts.	5 kts.	77 m	8 m	NA / 3040 cu. in
<b>EOL</b> 15 kts. WSW	1.5 m WS	0.5° Port	5.1 µB	5.1 kts.	5.1 kts.	77 m	8 m	NA / 3040 cu. in

### Recording Parameters

Recording System	Sercel Seal 408XL
Record Length	6000 ms
Sample Rate	2 ms
Start Of Data	50 ms before FTB
Low Cut Filter	4.7 Hz / 12dB Combined
Hi Cut Filter	200 Hz @ 370 dB / Octave
Tape Format	Demux. SEG D rev 1, 8058
Tape Brand	Imation BlackWatch 3590 10Gb
Polarity	First Break is Negative
Shot Point Interval	25m

### Source Parameters

Array Volume	3040 cubic inches
Operating Pressure	2000 psi +/- 10%
Array Configuration	3 Strings
Array Numbering	Stbd to Port / 1 to 3
Array Separation	10m
Source Depth	6 m +/- 1m
Center Source to Nav Mast	180m
Comment	

### Auxiliary Channels

Aux1: System St	Aux4: WB S1	Aux7:
Aux2: FTB	Aux5:	Aux8:
Aux3: 450 ms de	Aux6:	Aux9:

### Auxiliary Hydrophone Channels

Array 1	Array 2	Array 3
Aux13: Position 1	Aux19: Position 1	Aux25: Position 1
Aux14: Position 2	Aux20: Position 2	Aux26: Position 2
Aux15: Position 3	Aux21: Position 3	Aux27: Position 3
Aux16: Position 4	Aux22: Position 4	Aux28: Position 4
Aux17: Position 5	Aux23: Position 5	Aux29: Position 5
Aux18: Position 6	Aux24: Position 6	Aux30: Position 6

### Streamer Parameters

Number of Streamers	1
Streamer Length	6000m
Number Channels	480
Group Interval	12.5 m
Operating Depth	8 m +/- 1m
Crossline offset	NA
Offset CSCNG (inline)	145m (Centre of source to centre of near group)

**Line Status: Complete**

### Line Comments

String 1 NFH position 6 (Aux. 18) dead  
 SP range 1200 - 1264: occasional single trace noise spikes evident affecting traces 175-324 d/t debris/fishing gear.

### Bad Channels

Ch. 91, 337 failed capacitance.  
 Ch. 242, 452 failed leakage.  
 Ch. 452 failed Cutoff  
 Ch. 59 reversed polarity.  
 Ch. 7 noisy.

### Sequence breakdown

Start	End	Status	Comment
1001	1553	Prime	TDOB08-007

### Channels as recorded

AuxChannels: A1-A30	
Streamer1: 1-480	Streamer4:
Streamer2:	Streamer5:
Streamer3:	Streamer6:

GMT	Tape	Drive	File	SP	Event	Remarks
01:00					SoftStart	
	18	0/1	979-980		BOT	Noise files
01:39			981-1000	981-1000	FSP	Nav run in SPs
01:42			1001	1001	SOL	FGSP
02:52			1433	1433	LFFSP	
03:11			1553	1553	EOL	LGSP
	18	0/1	1554		EOT	Noise file

Abbreviations Used

SOL = Start of Line	BOT = Beginning of Tape	FGSP = First Good Shotpoint	FFFSP = First Full Fold Shotpoint	NDR = No Data Recorded
EOL = End of Line	EOT = End of Tape	LGSP = Last Good Shotpoint	LFFSP = Last Full Fold Shotpoint	FCSP = First Chargeable Shotpoint
FA = Feather Angle	SI = Seismic Interference	FOLSP = First Overlap SP	LOLSP = Last Overlap Shotpoint	LCSP = Last Chargeable
NTBP = Not To Be Processed	ITB = Internal Time Break	FTB = Field Time Break		