

Vessel: M/V Pacific Titan  
 Client: 3D Oil  
 Project #: 6374  
 Area: T41P

Preplotted LineName: **TDOB08-060**  
 Contractors Line Name: **TDOB08-060-041**

Direction: **238°**  
 Date Shot: **27 April 2008**

Party Chief: Haydn Brook Chief Obs: Tyrone Hackett Observers: Slawomir Korybalski, John Gracey, Ingvild Bostad

FS Time (UTC)	SOLTape#	First File	First Shot	First Shot File	FGSP	FGSP File	FGSP Time (UTC)	Swell Noise Levels
02:57	53	979	1724	981	1704	1001	03:00	<0.6% above 25µb

EOL Time (UTC)	EOLTape#	Last File	EOL SP	EOL File	LFFSP	LFFSP File	LFFSP Time (UTC)	Swell Noise Levels
04:57	53	1705	1001	1704	1121	1584	04:37	<0.6% above 25µb

	Wind Speed	Swell	Streamer Feather	Filtered Noise	Bottom Speed	Water Speed	Water Depth	Streamer Depth	Source Volume Stbd. Port
<b>SOL</b>	15 kts.W	2 m W	8.8 °Port	4.6 µB	4.9 kts.	4.8 kts.	75.1 m	8 m	NA / 3040 cu. in
<b>EOL</b>	15 kts.W	2 m W	3.0° Port	4.1 µB	4.8 kts.	5.0 kts.	77.6 m	8 m	NA / 3040 cu. in

### Recording Parameters

Recording System	Sercel Seal 408XL
Record Length	6000 ms
Sample Rate	2 ms
Start Of Data	50 ms before FTB
Low Cut Filter	4.7 Hz / 12dB Combined
Hi Cut Filter	200 Hz @ 370 dB / Octave
Tape Format	Demux. SEG D rev 1, 8058
Tape Brand	Imation BlackWatch 3590 10Gb
Polarity	First Break is Negative
Shot Point Interval	25m

### Streamer Parameters

Number of Streamers	1
Streamer Length	6000m
Number Channels	480
Group Interval	12.5 m
Operating Depth	8 m +/- 1m
Crossline offset	NA
Offset CSCNG (inline)	145m (Centre of source to centre of near group)

**Line Status:** Complete

### Source Parameters

Array Volume	3040 cubic inches
Operating Pressure	2000 psi +/- 10%
Array Configuration	3 Strings
Array Numbering	Stbd to Port / 1 to 3
Array Separation	10m
Source Depth	6 m +/- 1m
Center Source to Nav Mast	180m
Comment	

### Auxiliary Channels

Aux1: System St	Aux4: WB S1	Aux7:
Aux2: FTB	Aux5:	Aux8:
Aux3: 450 ms de	Aux6:	Aux9:

### Auxiliary Hydrophone Channels

Array 1	Array 2	Array 3
Aux13: Position 1	Aux19: Position 1	Aux25: Position 1
Aux14: Position 2	Aux20: Position 2	Aux26: Position 2
Aux15: Position 3	Aux21: Position 3	Aux27: Position 3
Aux16: Position 4	Aux22: Position 4	Aux28: Position 4
Aux17: Position 5	Aux23: Position 5	Aux29: Position 5
Aux18: Position 6	Aux24: Position 6	Aux30: Position 6

### Line Comments

String 1 NFH position 6 (Aux. 18) dead

### Bad Channels

Ch. 337 failed capacitance.  
 Ch. 242, 452 failed leakage.  
 Ch. 452 failed Cutoff  
 Ch. 59 reversed polarity.  
 Ch. 7 noisy

### Sequence breakdown

Start	End	Status	Comment
1704	1001	Prime	TDOB08-60

### Channels as recorded

AuxChannels: A1-A30	
Streamer1: 1-480	Streamer4:
Streamer2:	Streamer5:
Streamer3:	Streamer6:

GMT	Tape	Drive	File	SP	Event	Remarks
02:14					SoftStart	
	53	0/2	979-980		BOT	Noise files
02:57			981-1000	1724-1705	FSP	Nav run in SPs
03:00			1001	1704	SOL	FGSP
			1463	1242	GUN-BadShot	Autofire reported, gun header missing.
04:37			1584	1121	LFFSP	
			1678	1027	GUN-BadShot	Autofire reported, gun header missing.
04:57			1704	1001	EOL	LGSP
	53	0/2	1705		EOT	Noise file

Abbreviations Used

SOL = Start of Line	BOT = Beginning of Tape	FGSP = First Good Shotpoint	FFFSP = First Full Fold Shotpoint	NDR = No Data Recorded
EOL = End of Line	EOT = End of Tape	LGSP = Last Good Shotpoint	LFFSP = Last Full Fold Shotpoint	FCSP = First Chargeable Shotpoint
FA = Feather Angle	SI = Seismic Interference	FOLSP = First Overlap SP	LOLSP = Last Overlap Shotpoint	LCSP = Last Chargeable
NTBP = Not To Be Processed	ITB = Internal Time Break	FTB = Field Time Break		